

## YUKO UTTO 80W

### UNIVERSAL TRACTOR OIL FOR HYDRAULIC SYSTEMS AND TRANSMISSIONS

#### SPECIFICATIONS:

API GL-4

#### DESCRIPTION:

Universal UTTO-type tractor oil is designed for gearboxes, main gears, hydraulic systems lubrication, as well as wet brakes and clutches in tractors, forestry and agricultural machinery and construction machines. It is also used for heavy operating conditions.

YUKO AGRO UTTO produced using high quality mineral base oils and a multifunctional additive package.

#### CONFORMITY:

JOHN DEERE J20A, J20C    AGCO MF M1135, M1139, M1141    CASE MS1207, MS1210  
 ZF TE-ML 03E, 05F, 06D, 06K, 06M, 06N, 06R, 17E, 21F    ALLISON C4    Caterpillar TO-2    Case New Holland MAT-3525  
 M2C-134 A-D    FNHA-2-D.201.00    Volvo WB 101    Massey-Ferguson M1143 M1145    Ford

#### BENEFITS:

- Excellent anti-wear properties ensure maximum service life of machine parts;
- Application of friction modifiers allows to achieve the necessary level of frictional properties, ensuring efficient operation of wet brakes and clutch;
- Excellent anti-wear and extreme pressure properties ensure the protection of gears and hydraulic systems in a wide range of temperatures;
- Can be used as a general lubricant for the transmission and hydraulic system;
- Reliable protection of tractor units in various operating conditions.

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	9,7
Viscosity index	138
Alkalinity TBN, mg KOH/g	9.2
Flash point in open crucible, °C	220
Pour point, °C	-30

Packing	Vendor code	Barcode
Barrel metal 200l	011118	
Bucket tin 20l	011335	
In bulk	000000	

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.