

## ANTIFREEZE -40 (SUPER G11 BLUE)

### HIGH-QUALITY COOLANT LIQUID.

#### SPECIFICATIONS:

ASTM D3306    ASTM D4985

#### DESCRIPTION:

High-quality coolant liquid for modern gasoline and diesel engines (including engines made of light metals) which are operated in a variety of seasonal and climatic conditions.

YUKO Antifreeze Super G11 will protect your engine from freezing, overheating, corrosion and damaging deposits.

Provides reliable protection of the engine parts made of iron, aluminum, copper and steel. Made on monoethylene glycol and special anti-corrosion additives basis, produced by BASF.

Without glycerine.

#### APPROVAL:

G11

#### CONFORMITY:

VW/Audi/Seat/Skoda TL 774-C (G 11)    BMW GS 9400    MAN 324 NF    MB 325.0/325.2    MTU (MTL 5048)    BS 6580    Porsche  
 Saab 6901 599    Opel GM QL 130100    Cummins 85T8-2    Cummins CES 14603    Caterpillar    Detroit Diesel 7SE298  
 John Deere 8650-5    Case    New Holland    Volvo    MACK 014617004

#### BENEFITS:

- Excellent corrosion protection;
- Reduces possible cavitation damage for example damage of cooling liquid pump;
- Prevents foaming and compatible with rubber seals;
- Freezing and overheating protection due to high boiling point. Increased refrigerant strength;
- Corresponds to the best world G11 class liquids analogues.

#### TYPICAL CHARACTERISTICS:

Density at 20°C, g/cm <sup>3</sup>	1,040 – 1,100
Corrosive effect on metals	withstands
Copper, brass, steel, cast, iron, aluminum	0,2
Solder	0,3
Hydrogen index (pH), at 20°C	7,5-11
Alcalinity, cm <sup>3</sup> , min	2
Foam formation, cm <sup>3</sup> , max	30
Crystallization start temperature, °C	-38
Color	blue

Packing	Vendor code	Barcode
Canister plastic 20l	017542	482007024894
Barrel metal 200l	017739	482007024810
Canister plastic 10kg	019944	
Canister plastic 5kg	014030	482007024820
Canister plastic 1kg	015216	482007024447

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.