

DIESEL AGRO

SEASONAL MOTOR OIL FOR DIESEL ENGINES.

SPECIFICATIONS:

SAE 30 API CC

DESCRIPTION:

Mineral engine oil for low-pressure diesel engines, high-powered autotractor naturally aspirated diesel engines, stationary diesel engines operating at high speeds. In terms of its operational properties, it is equal to and even exceeds the properties of M-10G2k.

BENEFITS:

- Due to an excellent set of characteristics, the oil has the ability to neutralize acids that form during the operation of diesel engines;
- Good detergent-dispersant properties prevent the active formation of corrosion and other deposits;
- Guarantee of low sedimentation and high thermo-oxidative stability.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	910
Density at 20°C, kg/m ³	9,3 - 12,5
Viscosity index	85
Alkaline number, mg KOH/g	6,0
Flash point in an open crucible, °C	220
Pour point, °C	-18
Sulfate ash content,%	1,3

Packing	Vendor code	Barcode
Barrel metal 200l	22161	
Oilbox carton polyethylene 20l	22162	
Canister plastic 20l	22160	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.