

DIESEL SAE40

SEASONAL MOTOR OIL FOR DIESEL ENGINES.

SPECIFICATIONS:

SAE 40 API CC

DESCRIPTION:

Designed for medium-boosted naturally aspirated autotractor engines, diesel generators, pumping units, medium-boosted locomotive diesel engines operating at high loads on diesel fuel with a sulfur content of up to 0.5%.

BENEFITS:

- Protects engine parts from all types of deposits and corrosion;
- Has good detergent, antioxidant, extreme pressure and antiwear properties;
- Characterized by the ability to neutralize acids formed as a result of operation.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14,2
Density at 20°C, kg/m ³	895
Viscosity index	90
Alkaline number, mg KOH/g	7,15
Flash point in an open crucible, °C	240
Pour point, °C	-22
Sulfate ash content,%	0,99

Packing	Vendor code	Barcode
Barrel metal 200l	020537	
Canister plastic 20l	020536	4823110402412

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.