

## **BRAKE FLUID DOT 4**

### **UNIVERSAL SYNTHETIC BRAKE FLUID**

#### **SPECIFICATIONS:**

SAE J1704    ISO 4925 Class 4

#### **DESCRIPTION:**

Universal synthetic brake fluid for hydraulic brake systems and clutch drives of cars and trucks, motor vehicles, commercial and other specialized equipment.

Compatible with modern safety systems such as ABS, ESP, TSC, EBD, etc. Recommended for use in machinery equipped with disc and/or drum brake mechanisms, where the manufacturer allows the use of DOT 4 brake fluid. Ensures reliable operation of the braking system under standard and high loads in the widest temperature range.

The brake fluid drain interval in accordance with the recommendations of the equipment manufacturer.

#### **APPROVAL:**

JIS K 2233 Class 4    FMVSS 116 DOT 4

#### **CONFORMITY:**

Mercedes-Benz MB 331.0    VW-norm 501 14    Ford M6C62-A, M6C9103-A    Nissan KE903-99932    NH 800A (Honda)

Renault 41-02-001    Fiat 9.55597    Opel/GM 19 42 421    Toyota    Hyundai    Kia

Packing	Vendor code	Barcode
Tin can 910g	023248	4823110403433
Tin can 455g	023246	4823110403297

#### **STORAGE CONDITIONS:**

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.