

DYNAMIC 15W-40

MULTIPURPOSE ENGINE OIL WITH A HIGH CONTENT OF SYNTHETIC COMPONENTS

SPECIFICATIONS:

SAE 15W-40 API SG API CD

DESCRIPTION:

Intended for gasoline and diesel engines of passenger cars, vans and light trucks according to manufacturers' instructions. Produced of high-quality base oils with improved additives package containing synthetic components, providing high performance.

BENEFITS:

- Good anti-wear, antioxidant and dispersing properties;
- Increased engine cleanliness due to the high content of synthetic components;
- Easy cold start in winter;
- A wide range of packaging meets the requirements of any equipment.

TYPICAL CHARACTERISTICS:

Viscosity at 100°C mm ² /s	13.29
Density at at 20°C kg/m ³	874
Viscosity Index	148
TBN mg KOH/g	8.23
Flash point °C	217
Pour point °C	-34

Packing	Vendor code	Barcode
Barrel metal 200l	020523	
Canister plastic 20l	020522	
Canister plastic 5l	020519	
Canister plastic 4l	020516	
Canister plastic 1l	020513	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.