

## DYNAMIC 20W-50

### MULTIPURPOSE ENGINE OIL WITH A HIGH CONTENT OF SYNTHETIC COMPONENTS

#### SPECIFICATIONS:

SAE 20W-50    API SG    API CD

#### DESCRIPTION:

Intended for gasoline and diesel engines of passenger cars, vans and light trucks according to manufacturers' instructions. Produced of high-quality base oils with improved additives package containing synthetic components, providing high performance.

#### BENEFITS:

- Good anti-wear, antioxidant and dispersing properties;
- Increased engine cleanliness due to the high content of synthetic components;
- Easy cold start in winter;
- A wide range of packaging meets the requirements of any equipment.

#### TYPICAL CHARACTERISTICS:

Density at at 20°C kg/m <sup>3</sup>	885
Viscosity at 100°C mm <sup>2</sup> /s	19.9
Viscosity Index	125
TBN mg KOH/g	8.0
Pour point °C	-30

Packing	Vendor code	Barcode
Barrel metal 200l	020531	
Canister plastic 5l	020528	
Canister plastic 1l	020525	

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.