

EXTRA SYNT 0W-16

SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 0W-16 API SP ILSAC GF-6B

DESCRIPTION:

High-performance fully synthetic engine oil especially developed for American and Asian petrol engines of passenger cars, delivery vans and hybrids. Minimizes the risk of Low Speed Pre-Ignition in modern engines with GDI and TGDI. Ensures excellent low temperature flow characteristics to provide optimum protection for the engine at the cold start phase. Withstands extreme loads and safely handles high temperatures under all operating conditions.

CONFORMITY:

Ford GM Chrysler Toyota Lexus KIA Honda Nissan Mitsubishi Subaru Suzuki

BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

TYPICAL CHARACTERISTICS:

Viscosity mm ² /s at 100 °C	7,7
Density at 20 °C, kg/m ³	858
Viscosity Index	159
Pour point °C	-50
Flash point in open crucible, °C	225

Packing	Vendor code	Barcode
Canister plastic 5l	021175	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.