

## YUKO LITOL-24 EP

### MULTIPURPOSE EP GREASE

#### SPECIFICATIONS:

NLGI 2    ISO L-XDCEB 2    DIN KP2K-40

#### DESCRIPTION:

Multi-purpose grease LITOL-24 EP with extreme pressure additives used for lubrication of all types friction units: rolling and sliding bearings, joints, jag gears and other gears of industrial and other equipment of agricultural, automotive and construction machinery.

Temperature range: -40 °C ... +120 °C (short-term 130 °C).

#### BENEFITS:

- Improved wear and shock resistance at standard operating temperatures;
- Reduced washout by dirty and salt water due to excellent adhesion;
- Work at extremely low temperatures.

Packing	Vendor code	Barcode
Bucket plastic 17kg	025035	4823110406472
Bucket tin 17kg	022627	4823110402962
Bucket plastic 9kg	022618	4823110402955
Bucket plastic 2.7kg	022619	4823110402894

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.