

## MAX SYNTHETIC 0W-20

### SYNTHETIC MOTOR OIL.

#### SPECIFICATIONS:

SAE 0W-20    API SP    ILSAC GF-6A

#### DESCRIPTION:

High performance, fuel-efficient synthetic engine oil for the latest gasoline and diesel engines, equipped with the modern exhaust gas aftertreatment systems. Designed for vehicles, manufactured for the American and Asian markets (A&A).

Ideal for extended drain intervals (Longlife).

Approved for dynamic and extreme driving styles.

#### CONFORMITY:

GM dexos1 Gen 2    Ford WSS-M2C947-A, WSS-M2C962-A1    Chrysler MS-6395    FIAT 9.55535-CR1/GSX    Toyota    Nissan  
 Honda/Acura    Mitsubishi    Mazda    Suzuki    HYBRID Cars    Honda/Acura HTO-6    GM 6094 M    MB 229.6    BMW LL-01 FE  
 VOLVO 95200377    STJLR 03.5003

#### BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

#### TYPICAL CHARACTERISTICS:

Viscosity mm <sup>2</sup> /s at 100 °C	7,7
Density at 20°C, kg/m <sup>3</sup>	840
Viscosity Index	177
Flash point in open crucible, °C	225
Pour point °C	-44

Packing	Vendor code	Barcode
Tin can 4l	022063	4820070241521
Tin can 1l	021555	

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.