

## MAX SYNTHETIC 5W-30

### SYNTHETIC MOTOR OIL.

#### SPECIFICATIONS:

SAE 5W-30    API SP    ILSAC GF-6A

#### DESCRIPTION:

High performance, fuel-efficient synthetic engine oil for the latest gasoline and diesel engines, equipped with the modern exhaust gas aftertreatment systems. Contains PAO. Designed for vehicles, manufactured for the American and Asian markets (A&A).

Ideal for extended drain intervals (Longlife).

Approved for dynamic and extreme driving styles.

#### CONFORMITY:

GM dexos1 Gen 2    GM 6094M/4718M    Ford WSS-M2C929-A/946A, WSS-M2C945-A    Renault RN0700    Toyota    Nissan

Honda/Acura    Mitsubishi    Mazda    Suzuki    Chrysler MS 6395    Ford WSS M2C 912A/913A/B/C/D    Jaguar

Land Rover STJLR.03.5003

#### BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	10.2
Density at 20°C, kg/m <sup>3</sup>	855
Viscosity Index	175
Flash point in open crucible, °C	215
Pour point °C	-42

Packing	Vendor code	Barcode
Tin can 1l	021577	
Tin can 4l	022065	482311040152
Oilbox carton polyethylene 20l	020773	

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.