

MAX SYNTHETIC A&A 10W-30

FUEL-ECONOMY FULLY SYNTHETIC MOTOR OIL

SPECIFICATIONS:

SAE 10W-30 API SP ILSAC GF-6A

DESCRIPTION:

High performance, fuel-efficient synthetic engine oil for the latest gasoline and diesel engines, equipped with the modern exhaust gas aftertreatment systems. Contains PAO.

Designed for vehicles, manufactured for the American and Asian markets (A&A).

Ideal for extended drain intervals (Longlife). Approved for dynamic and extreme driving styles.

CONFORMITY:

GM dexos1 Gen 2 Ford WSS-M2C929-A Ford WSS-M2C946-A Ford WSS-M2C945-A Chrysler MS-6395 Nissan
 Honda/Acura Mitsubishi Mazda Toyota Suzuki

BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions

TYPICAL CHARACTERISTICS:

Viscosity mm ² /s at 100 °C	9.3-12.5
Density at 20 °C, kg/m ³	910
Viscosity Index	135
Pour point °C	-33
Flash point in open crucible, °C	200

Packing	Vendor code	Barcode
Canister plastic 4l	023042	
Canister plastic 1l	022735	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.