

MAX SYNTHETIC LL-4 0W-20

SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 0W-20 API SP ACEA C5 ILSAC GF-6A

DESCRIPTION:

PAO (Poly-alpha-olefin) based fully synthetic low friction motor oil for passenger car petrol and diesel engines with and without turbo-charging and direct injection. The low viscosity quickly lubricates and provides low friction resistance to reduce fuel consumption and pollutant emissions. Copes with all the thermal and mechanical loads that can occur in modern car engines that are designed for Fuel Economy. Specially developed for the latest Volkswagen Specification VW 508.00/509.00. .

APPROVAL:

Volkswagen VW 508.00 / 509.00

CONFORMITY:

Porsche C20

BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

TYPICAL CHARACTERISTICS:

Viscosity mm ² /s at 100 °C	6,3-9,3
Density at 20°C, kg/m ³	900
Viscosity Index	140
Pour point °C	-38
Flash point in open crucible, °C	200

Packing	Vendor code	Barcode
Canister plastic 5l	022645	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.