

MEGA DIESEL 10W-40

SEMI-SYNTHETIC ALL-SEASON MOTOR OIL FOR MODERN DIESEL ENGINES.

SPECIFICATIONS:

SAE 10W-40 API CI-4 API SL ACEA E7

DESCRIPTION:

The newest all-season semi-synthetic motor oil for long-distance and urban trucks, agricultural and construction machinery, buses and other commercial vehicles.

Produced of high-quality base oils with high-efficient modern additives package. Provides high antifriction, anticorrosion, detergent and antioxidizing oil properties throughout the service life.

Intended for year-round use incl. modern high-speed air and turbo diesel engines.

APPROVAL:

MB 228.3 Volvo VDS-3 CAT-ECF-1 CES 20078

CONFORMITY:

MB 228.3 MAN M3275-1 Volvo VDS-3 Renault RLD-2 CES 20076/77 MTU Type 2 ECF-1a DQC III-10

BENEFITS:

- Easy cold start in winter;
- Consistently high performance in various operating modes throughout the service life;
- Prevents high and low temperature deposits formation in the engine;
- Improved anti-foam properties, that significantly reduces foaming in the hydraulic drive system of the valves;
- Compatible with all engine sealings;
- High-class performance properties allow to apply Yuko Mega Diesel 10W-40 in the engines of most modern commercial vehicles.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14.8
Density at 20°C, kg/m ³	855
Viscosity index	168
Alkalinity, mg KOH/g	9,3
Flash point in open crucible, °C	222
Pour point, °C	-44

Packing	Vendor code	Barcode
Canister plastic 20l	021325	4820070240511
Barrel metal 200l	005274	482007024053

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.