

MEGA DIESEL 20W-50

MULTIGRADE DIESEL MOTOR OIL

SPECIFICATIONS:

SAE 20W-50 API CI-4 API SL ACEA A3/B4 ACEA E7

DESCRIPTION:

Hyper-viscosity high performance SHPD diesel motor oil. Is recommended for use in a wide range of applications and operating environments found in the on-road transport including heavy-duty and light diesel engines, heavy-duty and light petrol engines, and CNG & LPG operated vehicles.

CONFORMITY:

MB 228.3 MAN 3275-1 Cummins CES 20078 Volvo VDS-2, VDS-3 Renault RLD-2 Caterpillar ECF-1a

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	16.3-21.9
Density at 20°C, kg/m ³	910
Viscosity index	115
Alkalinity, mg KOH/g	7.5
Flash point in open crucible, °C	210
Pour point, °C	-20

Packing	Vendor code	Barcode
Barrel metal 200l	020914	
Canister plastic 20l	012093	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.