

MEGA HD 15W-40

ALL-SEASON MOTOR OIL FOR MODERN DIESEL ENGINES.

SPECIFICATIONS:

SAE 15W-40 API CI-4 API CF ACEA E4 ACEA E7

DESCRIPTION:

All-season motor oil for heavy duty diesel engines (including turbocharged with EGR and OMS) of agricultural, construction, mining vehicles and trucks.

CONFORMITY:

MB- 228.5 MAN M 3277 MAN M 3377 Volvo VDS-3 Renault RLD-2 DQC IV-10 CES 20077/78 MTU Type 3
 ECF -2 UHPD

BENEFITS:

- Easy start in winter;
- High and stable performance in all operating conditions;
- Excellent antifoam abilities;
- It prevents the formation of high and low temperature deposits;
- Compatible with the seals.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	15
Density at 20°C, kg/m ³	910
Viscosity index	120
Alkalinity, mg KOH/g	9,0
Flash point in open crucible, °C	200
Pour point, °C	-30

Packing	Vendor code	Barcode
Canister plastic 20l	15458	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.