

MEGA SYNT 15W-40

ADVANCED MULTIGRADE ENGINE OIL

SPECIFICATIONS:

SAE 15W-40 API CK-4 API SN ACEA E7 ACEA E9 JASO DH-2

DESCRIPTION:

Advanced multigrade motor oil for use in high-speed, cargo diesel engines, designed for longer drain intervals and more reliable engine and exhaust gas recirculation systems. It is used in engines equipped with exhaust gas pretreatment systems using Diesel Particulate Filters (DPF) and Oxidation Catalyst (DOC) in long-haul trucks and off-road vehicles, including construction, mining quarrying and agriculture.

CONFORMITY:

Mack EOS-4.5 Renault VI RLD-3 VOLVO VDS-4.5 Caterpillar ECF-3 Cummins CES 20081, CES 20086
 Detroit Diesel DDC 93K218, DDC 93K222 Deutz DQC III-10 LA IVECO MAN M 3275, M 3575, MB 228.31 MTU Typ 2.1

BENEFITS:

- Stable high performance under various operating conditions throughout the entire service life;
- High and stable performance in all operating modes;
- Absence of high-temperature and low-temperature deposits in the engine.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14.4
Density at 20°C, kg/m ³	895
Viscosity index	130
Alkalinity, mg KOH/g	9.0
Flash point in open crucible, °C	200
Pour point, °C	-25

Packing	Vendor code	Barcode
Canister plastic 20l	022851	
Barrel metal 200l	021489	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.