

MEGA SYNT 5W-30

ALL-SEASON MOTOR OIL FOR MODERN DIESEL ENGINES.

SPECIFICATIONS:

SAE 5W-30 API CK-4 ACEA E4 ACEA E6 ACEA E7

DESCRIPTION:

All-season motor oil for heavy duty diesel engines (including turbocharged with EGR and OMS) of agricultural, construction, mining vehicles and trucks.

APPROVAL:

MAN-Approval M 3775, MAN-Approval M 3677 DTFR 15C110 MB 228.51, MB 228.31 VOLVO VDS-4/VDS-4.5
 MACK EO-O PREMIUM PLUS RENAULT TRUCKS RLD-3 SCANIA LDF-4 DAF IVECO 18-1804

CONFORMITY:

MTU Type 2.1 DDC 93K218 Deutz DQC IV-10-LA CAT ECF-3 Cummins CES 20086 Cummins CES 20081

BENEFITS:

- Easy start in winter;
- High and stable performance in all operating conditions;
- Excellent antifoam abilities;
- It prevents the formation of high and low temperature deposits;
- Compatible with the seals.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm²/s 11,1
 Density at 20°C, kg/m³ 855
 Viscosity index 173
 Alkalinity, mg KOH/g 9,33
 Flash point in open crucible, °C 219
 Pour point, °C -43

Packing	Vendor code	Barcode
Canister plastic 20l	022850	482311040316

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.