

## POWER SYNT 4T 10W-30

### SEMISYNTHETIC MOTOR OIL FOR FOUR-STROKE ENGINES OF GENERATORS.

#### SPECIFICATIONS:

SAE 10W-30    API SN    API CF    JASO MA2    JASO T903:2016

#### DESCRIPTION:

It is used for lubrication of modern diesel and gasoline four-stroke engines of business and household generators.

Provides easy start, effective lubrication, even at low temperatures. It has an extended drain interval, according to the recommendations of the equipment manufacturer.

#### BENEFITS:

- Year-round use;
- Designed for the engines of frequently used power equipment;
- Due to the special high-viscosity formula, forms a durable oil film, capable of withstanding the continuous loads;
- Minimum evaporation loss rate, therefore - low consumption;
- Provides effective protection of the engine parts against corrosion and carbon formation;
- Improves engine compression, increasing its power.

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	10,8
Viscosity index	140
Alkalinity, mg KOH/g	6,7
Pour point, °C	-32

Packing	Vendor code	Barcode
Canister plastic 5l	026397	4823110402689
Canister plastic 1l	026394	4823110402658

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.