

POWER SYNT 4T 10W-40

SYNTHETIC MOTOR OIL FOR SMALL 4-STROKE ENGINES

SPECIFICATIONS:

SAE 10W-40 API SN API CF JASO MA2

DESCRIPTION:

Application: Designed for the lubrication of four-stroke engines in generators, lawnmowers, motor cultivators, motor mowers, mini-tractors, scooters, ATVs, and other modern small equipment, including those equipped with exhaust gas catalysts and turbochargers.

BENEFITS:

- Versatility: Optimal for a wide range of small-scale machinery.
- Wear Protection: Provides a stable lubricating film under peak loads.
- Engine Cleanliness: Effectively prevents the formation of carbon deposits and sludge.
- Easy Start: Excellent low-temperature fluidity ensures rapid lubrication of components during startup.
- JASO MA2 Compliance: Guarantees precise operation of "wet" clutches in power sports equipment.

TYPICAL CHARACTERISTICS:

Kinematic Viscosity at 100°C, mm ² /s	12.5 - 16.3
Density at 20°C, kg/m ³	900
Viscosity Index	140
Total Base Number (TBN), mg KOH/g	5
Flash Point (Open Cup), °C	200
Pour Point, °C	-32

Packing	Vendor code	Barcode
Canister plastic 1l	026709	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.