

REDUS UNIVERSAL

UNIVERSAL GEAR GREASE

SPECIFICATIONS:

NLGI 1 ISO 6743-9: L-XCCHB1 DIN KP1K-30

DESCRIPTION:

Universal grease is intended for gearboxes and internal moving parts of power tools, garden equipment and other mechanisms, equipment that works at high loads and temperatures.

Due to the EP-class additives effectively lubricates the surface, provides high antiwear and anti-corrosion properties. Provides long-term protection against water washing out and overheating of moving parts.

Each tube is equipped with a removable nose-applicator for convenient apply.

APPROVAL:

EP

BENEFITS:

- Reduces wear in high temperature and vibration;
- Mechanical and antioxidant stability;
- Excellent lubrication and low evaporation;
- Protection against rust and corrosion;
- Resistance to water washout.

TYPICAL CHARACTERISTICS:

Efficient viscosity at -20 °C, Pa • s-1, not more then	600
Penetration at 25°C, mm•10-1	310-340
Dropping Point, °C	180
Corrosion impact	stands
Colloid stability, %	18
Evaporation, not more then	2
Welding load, N, min	2450

Packing	Vendor code	Barcode
Tube plastic 0.125l	015181	482007024401

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.