

SUPER DIESEL 10W-40

ALL-SEASON MINERAL MOTOR OIL FOR MODERN DIESEL ENGINES.

SPECIFICATIONS:

SAE 10W-40 API CF-4 API SJ ACEA E2 ACEA E5

DESCRIPTION:

Intended for diesel engines of passenger cars, vans and trucks incl. powered by fuel with high sulphur content. Produced of mineral base oils with modern additives, providing oil performance stability throughout the whole service and shelf life.

CONFORMITY:

MB 228.1 MAN M271 Volvo VDS/VDS-2

BENEFITS:

- Excellent lubricating, detergent and anticorrosive properties
- Prevents high and low temperature deposits formation in the engine
- It is optimum for the most common diesel engine models
- Compatible with all engine sealings
- A wide range of packaging meets the requirements of any equipment

TYPICAL CHARACTERISTICS:

| | |
|--|------|
| Kinematic viscosity at 100°C, mm ² /s | 13,7 |
| Density at 20°C, kg/m ³ | 880 |
| Viscosity index | 152 |
| Alkalinity, mg KOH/g | 9,3 |
| Flash point in open crucible, °C | 218 |
| Pour point, °C | -39 |

| Packing | Vendor code | Barcode |
|----------------------|-------------|---------------|
| Canister plastic 20l | 021331 | 4823110401682 |
| Barrel metal 200l | 018082 | 482007024640 |

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.