

SUPER DIESEL 15W-40

ALL-SEASON MINERAL MOTOR OIL FOR MODERN DIESEL ENGINES.

SPECIFICATIONS:

SAE 15W-40 API CF-4 API SJ ACEA E2 ACEA E5

DESCRIPTION:

Intended for modern air and turbo diesel engines of passenger cars, vans and trucks incl. powered by fuel with high sulphur content. Produced of mineral base oils with modern additives, providing oil performance stability throughout the whole service and shelf life.

CONFORMITY:

MB 228.1 MAN M271 Volvo VDS/VDS-2

BENEFITS:

- Excellent lubricating, detergent and anticorrosive properties;
- Prevents high and low temperature deposits formation in the engine;
- Due to correspondence with quality degree API CF-4 it is optimum for the most common diesel engine models;
- Compatible with all engine sealings;
- A wide range of packaging meets the requirements of any equipment.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14,9
Density at 20°C, kg/m ³	870
Viscosity index	135
Alkalinity, mg KOH/g	9,8
Flash point in open crucible, °C	230
Pour point, °C	-38

Packing	Vendor code	Barcode
Canister plastic 20l	021332	4820070240658
Barrel metal 200l	000175	482007024012

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.