

SUPER GAS 10W-40

SEMI-SYNTHETIC ENGINE OIL FOR CARS EQUIPPED WITH LPG

SPECIFICATIONS:

SAE 10W-40 API SM API CF

DESCRIPTION:

Premium quality semi-synthetic motor oil intended for modern gasoline and diesel engines operating on natural gas (LPG - a mixture of propane and butane or CNG - methane) of passenger cars, vans and light trucks.

Produced from high quality base oils using a unique synthetic components that provides viscosity grade SAE 10W-40.

Compatible with injector engines, including turbocharged with intercooler and catalyst.

BENEFITS:

- High performance under different operating conditions - in a city and the "start-stop" mode;
- Good foaming and corrosion resistance, compatible with seal materials;
- Increased engine cleanliness due to the high content of synthetic components;
- Stable viscosity characteristics during the entire operation period due to the exceptional stability of all components;

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14,0
Density at 20°C, kg/m ³	872
Viscosity index	157
TBN mg KOH/g	5.6
Flash point in open crucible, °C	223
Pour point, °C	-40

Packing	Vendor code	Barcode
Canister plastic 1l	018079	482007024613
Bucket tin 20l	011906	482007024440
Canister plastic 4l	011887	482007024533
Canister plastic 5l	011809	482007024451

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.