

SUPER GAS 15W-40

SEMI-SYNTHETIC ENGINE OIL FOR CARS EQUIPPED WITH LPG

SPECIFICATIONS:

SAE 15W-40 API SM API CF

DESCRIPTION:

Semisynthetic motor oil specially produced for bi-fuel engines, equipped with LPG equipment (gas-petrol / gas-diesel) cars and vans that works in difficult operating conditions, urban traffic, "start-stop" mode. Effectively protects the engine against the high temperatures that occurs during the combustion of gaseous fuels.

Produced from high quality base oils using a unique synthetic components that provides viscosity grade SAE 15W-40.

APPROVAL:

MB 229.1 VW 501.00

BENEFITS:

- High performance under different operating conditions - in a city and the "start-stop" mode;
- Good foaming and corrosion resistance, compatible with seal materials;
- Increased engine cleanliness due to the high content of synthetic components;
- Stable viscosity characteristics during the entire operation period due to the exceptional stability of all components;

TYPICAL CHARACTERISTICS:

| | |
|--|--------|
| Kinematic viscosity at 100°C, mm ² /s | 15.08 |
| Density at 20°C, kg/m ³ | 855.90 |
| Viscosity index | 148 |
| Alkalinity, mg KOH/g | 5.78 |
| Flash point in open crucible, °C | 220 |
| Pour point, °C | -35 |

| Packing | Vendor code | Barcode |
|----------------------|-------------|---------|
| Barrel metal 200l | 014605 | |
| Canister plastic 20l | 011909 | |

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.