

SUPER SYNTHETIC 0W-40

FULLY SYNTHETIC ENGINE OIL OF HIGH-TECH GRADE

SPECIFICATIONS:

SAE 0W-40 API SN API CF ACEA A3/B4 ILSAC GF-6A

DESCRIPTION:

High performance fully synthetic engine oil of High-Tech grade. Designed for the latest gas and diesel engines of passenger cars and buses. Compatible with injector and multivalve engines including turbocharged, equipped with intercooler and catalyzer.

CONFORMITY:

BMW Longlife-01 MB 229.3 MB 229.5 VW 502.00 VW 505.00 Porsche A40

BENEFITS:

- Ensures a stable lubricating film over a wide temperature range;
- Reduction of fuel consumption and car exhaust emissions
- Excellent mechanical High Temperature High Shear (HTHS) rate stability throughout the entire service life.

TYPICAL CHARACTERISTICS:

Viscosity mm ² /s at 100 °C	12,5 - 16,3
Density at 20°C, kg/m ³	900
Viscosity Index	140
Pour point °C	-39
Flash point in open crucible, °C	200

Packing	Vendor code	Barcode
Canister plastic 5l	013628	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.