

SUPER SYNTHETIC C4 5W-30

SYNTHETIC MOTOR OIL.

SPECIFICATIONS:

SAE 5W-30 API SN API CF ACEA C4

DESCRIPTION:

Longlife fuel-economy fully synthetic engine oil for all types of cars with petrol and diesel engines (including fuel injected engines, multivalve engines with or without turbo-charge, with or without catalytic converters of exhaust gas, with or without DPF).

Produced of high-quality synthetic base oils with additives, providing high performance of engine within a wide temperature range and extending its service life. Meets the requirements of Longlife service interval (WIV) of VAG group.

CONFORMITY:

MB 226.51 MB 229.51 Renault RN 0720 Fiat 9.55535-S4

BENEFITS:

- Extreme wear protection & excellent viscosity-temperature behaviour
- Minimal frictional loss & Very high cleaning capability
- Low volatilization loss & High oxidation and temperature stability
- Reduces fuel consumption according API EC and reduces exhaust emission
- Excellent cold starting properties – rapid supply of all points of lubrication
- Very good operating reliability & multigrade usage
- Optimal engine cleanliness & lowest oil consumption
- High margin of performance & product stability
- Extended oil change intervals & prevents black sludge formation

TYPICAL CHARACTERISTICS:

Density at at 20°C kg/m ³	900
Flash point °C	200
Pour point °C	-35
Viscosity at 100°C mm ² /s 9,3 - 12,5	
Viscosity Index	140
TBN mg KOH/g	5,0

Packing	Vendor code	Barcode
Canister plastic 1l	027125	
Canister plastic 5l	027006	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.