

SYNTHETIC 4T 5W-40

PREMIUM SYNTHETIC MULTIGRADE MOTOR OIL FOR 4-STROKE ENGINES.

SPECIFICATIONS:

SAE 5W-40 API SN JASO MA2

DESCRIPTION:

Premium synthetic multigrade motor oil for 4-stroke engines of motorcycles, ATV, scooters and other motor transport with all types of coupling engagement, transportable equipment.

The product provides minimal exhaust smoking and toxicity. Produced of high-quality synthetic base oils with additives, providing high performance of engine within a wide temperature range and extending its service life.

BENEFITS:

- Provides the best lubricating, anti-wear, anti-corrosion and cleaning characteristics, including under extreme loads;
- Has the optimal level of quality for four-stroke engines of the most modern technology;
- Provides minimal exhaust smoke, which allows the use of oil in conditions of strict environmental standards;
- Contains a complex of active additives of the latest generation, which ensure increased cleanliness of the engine;
- Mixes well with fuel even at low temperatures.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	9.3-12.5
Density at 20°C, kg/m ³	900
Viscosity index	140
Alkaline number, mg KOH/g	5.0
Flash point in an open crucible, °C	200
Pour point, °C	-32

Packing	Vendor code	Barcode
Tin can 1l	021589	4823110401774

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.