

## SYNTHETIC DIESEL 5W-40

### SYNTHETIC ENGINE OIL DESIGNED FOR MODERN DIESEL ENGINES

#### SPECIFICATIONS:

SAE 5W-40    API CI-4    API SL    ACEA E4    ACEA E6    ACEA E7    ACEA E9

#### DESCRIPTION:

Used for diesel engines of magistral trucks, working at high loads, high speeds and extended lifetime, with a change interval up to 100,000 km.

#### BENEFITS:

- Prolonged oil drain interval up to 100,000 km. mileage when using the original consumables and high-quality fuel;
- High stable performance under any operating conditions;
- Excludes lack deposits in the engine while operating at a high-temperature or low-temperature;

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	14,3
Density at 20 °C, kg/m <sup>3</sup>	844
Viscosity index	161
TBN mg KOH/g	9,8
Flash Point COC °C	227
Pour point, °C	-41

Packing	Vendor code	Barcode
Barrel metal 200l	017193	4823110401033
Canister plastic 20l	017192	4823110401026

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.