

TRANS 75W-80

UNIVERSAL SEMI-SYNTHETIC TRANSMISSION OIL.

SPECIFICATIONS:

SAE 75W-80 API GL-4

DESCRIPTION:

Used in modern mechanical transmissions of passenger cars and trucks, differentials, transfer cases, and other units, where the use of transmission oil of API GL-4 grade is recommended.

Produced of high-quality base oils with modern additives package.

BENEFITS:

- Good lubrication and easy cold start including at low temperatures throughout the service life;
- Excellent frictional properties ensure smooth gear change and quiet operation;
- Consistently high performance in various operating modes;
- A high level of wear protection within a wide load range;
- Has increased oil drain period due to the high thermal stability.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	8,8
Density at 20°C, kg/m ³	855
Viscosity index	216
Flash point in open crucible, °C	210
Pour point, °C	-46

Packing	Vendor code	Barcode
Canister plastic 1l	021618	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.