

TRANS 80W-90

UNIVERSAL ALL-SEASON TRANSMISSION OIL.

SPECIFICATIONS:

SAE 80W-90 API GL-4

DESCRIPTION:

Used in mechanical transmissions of passenger cars and trucks, differentials, transfer gears, heavy duty transmissions, and other units where oil grade API GL-4 recommended.

CONFORMITY:

ZF TE-ML 16K 08 02L 01L Volvo 97305 DAF Iveco MB 235.11 MAN 341 Type E3 MAN 341 Type Z4

Renault Axle (B0032/2 Annex3)

BENEFITS:

- High performance within wide range of operating conditions for a long time;
- Good anti-foam and anti-corrosion properties, compatible with seal materials;
- A high level of wear protection within a wide load range;
- The modern package of extreme pressure additives provides a high level of protection for various loads, including impact loads.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100 °C, mm ² /s	16,4
Density at 20 °C, kg/m ³	891
Viscosity index	92
Flash point in open crucible, °C	210
Pour point, °C	-28

Packing	Vendor code	Barcode
Canister plastic 1l	012160	482007024445

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.