

## TRANS HD 75W-90

### UNIVERSAL HEAVY DUTY TRANSMISSION OIL.

#### SPECIFICATIONS:

SAE 75W-90    API GL-5

#### DESCRIPTION:

Used in modern mechanical transmissions of passenger cars and trucks, differentials, transfer cases, and other units, where the use of transmission oil of API GL-5 grade is recommended.

Produced of high-quality base oils with modern additives package.

#### BENEFITS:

- A high level of wear protection within a wide load range;
- Good lubrication and easy cold start including at low temperatures throughout the service life;
- Consistently high performance in various operating modes;
- Has increased oil drain period due to the high thermal stability.
- Excellent frictional properties ensure smooth gear change and quiet operation;

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm <sup>2</sup> /s	14,5
Density at 20°C, kg/m <sup>3</sup>	875
Viscosity index	159
Flash point in an open crucible, °C	216
Freezing point, °C, not higher	-40

Packing	Vendor code	Barcode
Bucket tin 20l	020486	
Bucket tin 20l	020481	
Canister plastic 1kg	020477	

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.