

TRANS HD 80W-90

SYNTHETIC HEAVY DUTY TRANSMISSION OIL.

SPECIFICATIONS:

SAE 80W-90 API GL-5

DESCRIPTION:

Used in modern highly loaded mechanisms of cars and trucks - mechanical gearboxes, main gearboxes, differentials, transfer cases, as well as in all other units where the use of transmission oil of API GL-5 grade is recommended.

Produced of high-quality synthetic base oils with modern additives package.

CONFORMITY:

MAN 342 N / 342 TypM2 MB 235.0, 235.6 ROCKWELL VOLVO 97310, 97313

FORD M-2C-9022 F / SM-2C-1011-A / EST-M2C-108C ZF TE-ML 05A, 07A, 08, 12E, 16B/C/D, 17B, 19B, 21A Renault MIL-L-2105D

BENEFITS:

- Good lubrication and easy cold start including at low temperatures throughout the service life;
- Excellent frictional properties ensure smooth gear change and quiet operation;
- Consistently high performance in various operating modes;
- A high level of wear protection within a wide load range;
- Has increased oil drain period due to the high thermal stability.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	15,8
Density at 20°C, kg/m ³	880
Viscosity index	147
Flash point in open crucible, °C	206
Pour point, °C	-38

Packing	Vendor code	Barcode
Canister plastic 1l	020482	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.