

DIESEL SAE30

SEASONAL MOTOR OIL FOR DIESEL ENGINES.

SPECIFICATIONS:

SAE 30 API CD

DESCRIPTION:

Seasonal mineral motor oil for high-performance diesel engines, stationary diesel engines and diesel generators, including moderate turbochargers, operating in difficult operating conditions.

BENEFITS:

- A large reserve of alkalinity provides excellent washing and neutralizing properties of the oil throughout the entire period of operation;
- Improved anti-wear and anti-corrosion properties;
- Possesses high thermooxidative stability;
- Provides long mileage between oil changes;
- A wide range of packaging forms meets the needs of any technique.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	13,1
Density at 20°C, kg/m ³	897
Viscosity index	93
Alkaline number, mg KOH/g	10,5
Flash point in an open crucible, °C	250
Pour point, °C	-32
Sulfate ash content,%	1,4

Packing	Vendor code	Barcode
Canister plastic 5l	022590	4823110402856
Barrel metal 200l	022571	4823110402870
Canister plastic 20l	022570	4823110402863

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.