

VUKO PRESSURE 46

SPECIFICATIONS:

ISO 46 DIN DIN 51506 VDL 46 (VBL, VCL)

DESCRIPTION:

Description: Designed for the lubrication of rotary vane and screw air compressors equipped with oil injection or oil-filled systems. It is suitable for continuously operating compressors under high-temperature conditions, withstanding short-term peaks of up to +150°C on the discharge line.

CONFORMITY:

ISO 6743-3 DAH

BENEFITS:

- Prevents foaming and possesses outstanding water separation properties.
- Excellent deaeration properties and low volatility.
- An enhanced alternative to traditional compressor oil: KP-8S (ISO 46).

TYPICAL CHARACTERISTICS:

Kinematic Viscosity at 40°C, mm ² /s	41.4 – 50.6
Density at 20°C, kg/m ³	876.4
Viscosity Index	103
Acid Number, mg KOH/g	0.12
Flash Point (Open Cup), °C	223
Pour Point, °C	-34

Packing	Vendor code	Barcode
Canister plastic 20l	27295	
Barrel metal 200l	27296	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.