

## VUKO PRESSURE 68

### SPECIFICATIONS:

ISO 68

### DESCRIPTION:

Designed for the lubrication of rotary vane and screw air compressors, including oil-injected and oil-filled systems. Recommended for continuous operation under heavy-duty conditions and elevated temperatures, withstanding short-term peaks of up to +150°C on the discharge line. It ensures a stable lubricating film, efficient heat dissipation, and reliable wear protection.

### CONFORMITY:

ISO 6743-3 DAH    DIN 51506 VDL

### BENEFITS:

- High thermal and oxidation stability with low deposit formation.
- Excellent deaeration and anti-foam properties.
- Superior water separation characteristics.
- Effective protection against wear and corrosion.
- Suitable for extended periods of continuous operation.

### TYPICAL CHARACTERISTICS:

Kinematic Viscosity at 40°C, mm <sup>2</sup> /s	61.2 – 74.8
Density at 20°C, kg/m <sup>3</sup>	876.2
Viscosity Index	104
Acid Number, mg KOH/g	0.11
Flash Point (Open Cup), °C	230
Pour Point, °C	-26

Packing	Vendor code	Barcode
Canister plastic 20l	27297	
Barrel metal 200l	0027297	

### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.