

VUKO TRANS CX 50

SPECIFICATIONS:

SAE 80W-90 API GL-5

DESCRIPTION:

Used for the lubrication of transmissions in trucks, passenger cars, and other equipment where GL-5 class gear oils are recommended. Specifically designed for hypoid gears operating under shock loads with contact stresses exceeding 3000 MPa and bulk oil temperatures up to 150°C.

CONFORMITY:

MIL-L-2105D MB 235.6 MAN 342 ML ZF TE-ML 05A-07A-12A-16C-17B

BENEFITS:

- Highest level of performance characteristics.
- Smooth gear shifting and quiet transmission operation.
- Modern additive package ensures a high level of protection under various conditions, including shock loads.

TYPICAL CHARACTERISTICS:

Kinematic Viscosity at 100°C, mm ² /s	15.72
Density at 20°C, kg/m ³	891.1
Viscosity Index	92
Acid Number, mg KOH/g	0.35
Flash Point (Open Cup), °C	220
Pour Point, °C	-25

Packing	Vendor code	Barcode
Barrel metal 200l	027115	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.