

YUKO ATF CVT

SPECIAL AUTOMATIC TRANSMISSION FLUID

DESCRIPTION:

Used in variators with both belt and chain drive. Recommended for use in CVTs of American, Asian and European manufacturers and other transmissions, where the use of ATF CVT is provided and recommended by the OEM manual. It contains the latest package of anti-wear additives that ensures high torque and reduces wear.

APPROVAL:

Toyota TC/CVT FE Mitsubishi CVTF-J1/SP III MB 236.20 Honda HMMF/HCF2/Z1 Subaru Lineartronic
 CV-30/CVTF/CVTF II/E-CVT/iCVT Nissan NS-1/NS-2 Hyundai/KIA SP-CVT1 Suzuki TC/NS-2/CVT

CONFORMITY:

GM DEX-CVT Ford WSS-M2C928-A Toyota TC/CVT FE Mitsubishi CVTF-J1/SP III MB 236.20 Honda HMMF/HCF2/Z1
 Subaru Lineartronic CV-30/CVTF/CVTF II/E-CVT/iCVT Nissan NS-1/NS-2 Hyundai/KIA SP-CVT1 Suzuki TC/NS-2/CVT

BENEFITS:

- Has a high thermal, oxidation stability and excellent pumpability (low temperature fluidity), providing uninterrupted operation of the machinery at extremely low temperatures;
- Excellent frictional properties;
- Ensures quiet operation;
- Extends transmission service life.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s#ASTM D445 or GOST 33	7.5
Density at 20°C, kg/m ³ #ASTM D1298 or GOST 3900	843,2
Viscosity index#ASTM D2270 or DSTU GOST 25371	185
Flash point in open crucible, °C#ASTM D92 or GOST 4333	200
Pour point, °C#ASTM D97 of GOST 20287	-50

Packing	Vendor code	Barcode
Tin can 1l	021723	4820070245172

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.