

YUKO ATF DSG

HIGH-PERFORMANCE PREMIUM-GRADE SYNTHETIC FLUID

DESCRIPTION:

High-performance premium-grade synthetic fluid for dual-clutch transmissions. The product is designed for robotic systems with friction discs immersed in oil, which ensure uninterrupted DSG / DCT operation in difficult operating conditions.

CONFORMITY:

VW G 052 178/182 VW TL 052 182 VW G 052 512/513/529 VW G 052 726/798/171 VW G 055 532
 BMW DCTF-1/ MTF-LT-5 PSA 9734.S2 Renault Bot 450 Volvo Bot 341, 161838 Ford WSS M2C-936-A
 Ford WSS-M2C-200-D2 MB 236.25- MB 236.21 Mitsubishi Diamond Queen SSTF-1

BENEFITS:

- Has a high thermal, oxidation stability and excellent pumpability (low temperature fluidity), providing uninterrupted operation of the machinery at extremely low temperatures;
- Excellent frictional properties;
- Ensures quiet operation;
- Extends transmission service life.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s#ASTM D445 or GOST 33	7,0 – 9,0
Density at 20°C, kg/m ³ #ASTM D1298 or GOST 3900	890
Viscosity index#ASTM D2270 or DSTU GOST 25371	160
Flash point in open crucible, °C#ASTM D92 or GOST 4333	185
Pour point, °C#ASTM D97 of GOST 20287	- 45

Packing	Vendor code	Barcode
Canister plastic 1l	019458	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.