

ATF III

MULTIPURPOSE ALL-SEASON POWER FLUID FOR AUTOMATIC GEARBOXES

DESCRIPTION:

Intended for automatic gearboxes, transmissions, servo drives (power steering) of passenger cars and trucks, buses, special vehicles, other hydraulic systems, where Dexron® III or Dexron® II fluids are recommended.

Produced on basis of foreign components. Coloured red.

APPROVAL:

GM DEXRON - III G Ford MERCON V Allison C-4 MAN 339 type Z-2 / Z1 / V1 Volvo 97340 ZF TE-ML 04D
 ZF TE-ML 14B ZF TE-ML 16L ZF TE-ML 17C

BENEFITS:

- Has a high thermal, oxidation stability and excellent pumpability (low temperature fluidity), providing uninterrupted operation of the machinery at extremely low temperatures;
- Provides easiness and smoothness of gear change in various operating modes;
- Ensures quiet operation;
- Excellent frictional properties;
- Extends transmission service life.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	7.5
Density at 20°C, kg/m ³	850
Viscosity index	170
Flash point in open crucible, °C	205
Pour point, °C	-52

Packing	Vendor code	Barcode
Canister plastic 20l	009127	482007024201
Tin can 1l	021725	4820070241914

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.