

DYNAMIC 10W-40

UNIVERSAL MOTOR OIL WITH HIGH CONTENT OF SYNTHETIC COMPONENTS.

SPECIFICATIONS:

SAE 10W-40 API SG API CD

DESCRIPTION:

Intended for gasoline and diesel engines of passenger cars, vans and light trucks according to manufacturers' instructions. Produced of high-quality base oils with improved additives package containing synthetic components, providing high performance.

BENEFITS:

- Good anti-wear, antioxidant and dispersing properties;
- Increased engine cleanliness due to the high content of synthetic components;
- Easy cold start in winter;
- A wide range of packaging meets the requirements of any equipment.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	14,2
Density at 20°C, kg/m ³	875
Viscosity index	148
TBN mg KOH/g	7.9
Flash point in open crucible, °C	217
Pour point, °C	-34

Packing	Vendor code	Barcode
Barrel metal 200l	006081	482007024026
Canister plastic 5l	006080	482007024208
Canister plastic 4l	006125	482007024207
Canister plastic 1l	006079	482007024206

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.