

YUKO EOM-1 (ISO 32)

WATER-SOLUBLE LUBRICATING COOLANT.

SPECIFICATIONS:

ISO 32

DESCRIPTION:

Emulsol, used in the form of 5% emulsion. Intended for use in operation of sharpening, milling, drilling, reaming, shaping, screw cutting, broaching, grinding of cast iron, carbon, low and middle alloyed structural steel, some alloys and non-ferrous metals.

BENEFITS:

- A high biostability;
- Improved efficiency and durability;
- Absence of heavy metals;
- Safe for environment and human health;
- Good wetting and cleaning properties;
- Improved treatment quality and reduced equipment wear;
- Excellent corrosion protection.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 50 °C, mm/s	39,5
Density at 20 °C, kg/m	880
Corrosive effect on metals	stands
pH value of 5% operation emulsion, pH units	9.9

Packing	Vendor code	Barcode
Canister plastic 20l	006232	482007024131

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.