

YUKO HYDROL HM 46

HYDRAULIC OIL.

SPECIFICATIONS:

ISO 46 ISO HM DIN HLP

DESCRIPTION:

Intended for hydraulic systems of various domestic and foreign equipment, requiring the high-class purity oils. Used in the equipment with pumps of all types, operating under the pressure over 25MPa.

Produced of high-quality extra-pure base oils with additives package.

BENEFITS:

- High grade purity provides a high level of oil performance;
- Excellent low-temperature and anticorrosion properties;
- High oxidation and foaming resistance;
- High level of anti-wear protection within a wide load range.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 40°C, mm ² /s	45.5
Density at 20°C, kg/m ³	890
Viscosity index	98
Acid index, mg KOH/g	0.65
Flash point in open crucible, °C	218
Pour point, °C	-32

Packing	Vendor code	Barcode
Oilbox carton polyethylene 20l	022163	4823110402382
Barrel metal 200l	005505	482007024107
Canister plastic 20l	021338	482007024378

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.