

HYDROL HM 68

HIGH QUALITY HYDRAULIC OIL

SPECIFICATIONS:

ISO 68 ISO HM DIN HLP

DESCRIPTION:

YUKO HYDROL HM 68 is used in hydraulic systems of industrial equipment, machines and vehicles where high-quality hydraulic oil recommended.

Produced from high quality mineral base oils with a balanced additive system containing antioxidant, antiwear, anti-corrosion and anti-foam additives.

Successfully applied wherever a long service life is required, excellent filterability, good hydrolytic stability and high water separation properties.

BENEFITS:

- Without zinc, calcium and other metals;
- Excellent wear protection;
- Excellent hydrolytic stability;
- Long-term oxidation resistance provides a long service life;
- Low foaming;
- Good filterability.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 40°C, mm ² /s	65,2
Viscosity index	92
Density at 15°C, kg/m ³	883
Acid index, mg KOH/g max	0.65
Flash point in open crucible, °C	215
Pour point, °C	-32

Packing	Vendor code	Barcode
Bucket tin 20l	017194	482007024527
Barrel metal 200l	009916	482007024532

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.