

MASTER SYNT 4T 10W-30

SEMISYNTHETIC MOTOR OIL FOR FOUR-STROKE ENGINES.

SPECIFICATIONS:

SAE 10W-30 API SL API CF JASO MA2 JASO T903:2016

DESCRIPTION:

Used for lubricating systems of modern four-stroke engines of garden machinery and power equipment: mowers, cultivators, generators, motor pumps, snow-removing machines and other four-stroke machinery.

A modern additives package, provides performance stability throughout the service life, ensuring a high level of reliability and low-temperatures stability. Minimizes exhaust smoking and emissions toxicity.

BENEFITS:

- Year-round use;
- Designed for the engines of frequently used garden machinery and power equipment;
- Due to the special high-viscosity formula, forms a durable oil film, capable of withstanding the continuous loads;
- Minimum evaporation loss rate, therefore - low consumption;
- Provides effective protection of the engine parts against corrosion and carbon formation;
- Improves engine compression, increasing its power.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	10,8
Viscosity index	140
Alkalinity, mg KOH/g	6,7
Pour point, °C	-32

Packing	Vendor code	Barcode
Oilbox carton polyethylene 20l	022523	4823110402726
Canister plastic 1l	010215	4820070240450
Tin can 600ml	023243	4823110403273

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.