

MOTOMIX 2T

MINERAL MOTOR OIL FOR TWO STROKE ENGINES.

SPECIFICATIONS:

API TC JASO FB

DESCRIPTION:

Intended for lubricating systems of air-cooled two stroke engines of modern motorcycles, motorbikes, chainsaws and other machinery. Used as a component in oil-fuel blend in a ratio recommended by machines manufacturer. Standard injection varies from 1:32 to 1:50.

BENEFITS:

- Provides good lubricating, anti-wear, anticorrosion and detergent properties due to the active additives package;
- Provide carbon removal from the combustion chamber;
- The possibility of year-round use;
- Provides long service life of ignition plug;
- Minimizes maintenance costs.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	8.5
Density at 20°C, kg/m ³	890
Viscosity index	90
Alkalinity, mg KOH/g	0.85
Flash point in open crucible, °C	215
Pour point, °C	-25

Packing	Vendor code	Barcode
Canister plastic 1l	000605	482007024081
Aerosol can 500 ml	023244	4823110403266

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.