

## YUKO MS-20 (CB 50)

### MOTOR OIL FOR EQUIPMENT DIESEL ENGINES.

#### SPECIFICATIONS:

SAE 50 API CB

#### DESCRIPTION:

It is used for engines and gearboxes of ground equipment used in metallurgical, mining and woodworking enterprises, as well as for other similar equipment.

It is produced from mineral base oils with additives.

#### BENEFITS:

- High lubricating capacity;
- Oil is not aggressive to metals, alloys and other structural materials;
- High thermal and thermal oxidation stability.

#### TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100 °C, mm <sup>2</sup> /s	21.1
Viscosity index, min	88
Acid index, mg KOH/g	0.024
Flash point in open crucible, °C	250
Pour point, °C	-15

Packing	Vendor code	Barcode
Canister plastic 20l	011123	4820070243604
Barrel metal 200l	005078	482007024085

#### STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.