

YUKO RUST REMOVER

DESCRIPTION:

Fast-acting cleaner for dissolving and removing rust, unblocking threaded and moving connections. Prevents corrosion, eliminates squeaks, displaces moisture, and ensures effective operation of mechanisms across a wide temperature range. Suitable for professional and household use.

Method of Application: Shake the can. Spray the product from a distance of 20 cm onto parts and connections, allowing time for active penetration. Remove any excess with a dry cloth. Repeat treatment if necessary.

Storage Conditions: Keep away from direct sunlight and heating above 50 °C! Do not spray near open flames, hot surfaces, or other ignition sources. Do not inhale, disassemble, or deform! Dispose of the spent can as household waste! Store at temperatures from -20 °C to +50 °C.

CAUTION: pressurized can! DO NOT PUNCTURE OR INCINERATE! FLAMMABLE! Guaranteed shelf life is 5 years from the date of manufacture, provided storage rules are observed and packaging remains intact.

BENEFITS:

- Quickly dissolves and removes rust.
- Unblocks rusted threaded and moving connections.
- Prevents further corrosion.
- Eliminates squeaks.
- Displaces moisture.
- Works effectively across a wide temperature range.
- Suitable for professional and household use.

TYPICAL CHARACTERISTICS:

Excess pressure in aerosol can at 20 °C	0.2-0.5 MPa, 2.0-5.0 kgf/cm ³
Viscosity at 20 °C, cP, not more than	500
Relative density at 20 °C, g/ml	0.8-0.9
Vapor pressure at 20 °C, kPa	350
Degree of content evacuation from aerosol can, %, not less than	95
Solubility in water	Insoluble

Packing	Vendor code	Barcode
Balloon tin 0.4l	025963	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.