

SCOOTER SYNT 2T (FC)

SEMISYNTHETIC MOTOR OIL FOR TWO-STROKE ROAD MACHINERY.

SPECIFICATIONS:

API TC JASO FC

DESCRIPTION:

Intended for two-stroke engines of air-cooled road machinery such as: modern motorcycles, motorbikes, scooters, snowmobiles and other two-stroke machinery.

Used as a component in oil-fuel blend in a ratio recommended by machines manufacturer. Standard injection varies from 1:32 to 1:50.

Produced of high-quality base oils with selected active additives package.

BENEFITS:

- Provides best lubricating, anti-wear, anticorrosion and detergent properties incl. extreme loads;
- Has optimal quality level for two-stroke engines of modern machinery;
- Ideal for vehicles manufactured in Japan, China and South-East Asia, as it corresponds to specifications of JASO FC (Japan);
- Minimizes exhaust smoking, which allows to use this oil in conditions of strict environmental regulations;
- The possibility of application in separate lubricating systems for two-stroke engines;
- Contains active additives package of new generation, providing increased engine cleanliness;
- Good fuel-miscible even at low temperatures.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	7,7
Density at 20°C, kg/m ³	875
Viscosity index	98
Alkalinity, mg KOH/g	0,8
Flash point in open crucible, °C	110
Pour point, °C	-15

Packing	Vendor code	Barcode
Tin can 1l	021591	

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.