

SEMISYNTHETIC 10W-40

SEMISYNTHETIC PREMIUM MOTOR OIL.

SPECIFICATIONS:

SAE 10W-40 API SN API CF ACEA A3/B4

DESCRIPTION:

Intended for modern gasoline and diesel engines of passenger cars and vans (injector, multivalve, turbocharged, including fitted with exhaust fumes catalysts). It is an optimum choice for vast majority of foreign passenger cars and vans.

Produced of high-quality base oils with well-balanced additives package, providing good antifriktion, anticorrosion, detergent and antioxidizing properties.

CONFORMITY:

VW 502 00/505 00 MB 229.1, 229.3 PSA B71 2300 BMW Special Renault RN 0700, RN 0710 Fiat 9.55535 D2/G2

BENEFITS:

- Consistently high performance in various operating modes;
- Easy cold start in winter;
- Prevents high and low temperature deposits formation in the engine;
- High-class performance properties allows using YUKO Semisynthetic 10W-40 in the engines of the most modern cars;
- Compatible with all engine sealings;
- A wide range of packaging meets the requirements of any equipment.

TYPICAL CHARACTERISTICS:

Kinematic viscosity at 100°C, mm ² /s	13.2
Density at 20°C, kg/m ³	855
Viscosity index	151
TBN mg KOH/g	9.3
Flash point in open crucible, °C	224
Pour point, °C	-36

Packing	Vendor code	Barcode
Tin can 4l	021601	4820070240153
Tin can 1l	021579	4820070240160

STORAGE CONDITIONS:

Do not mix with solvents, automotive fluids. Protect from direct sunlight and precipitation in a closed container at a temperature not exceeding +60°C. In case of contact with skin or mucous membranes, rinse with water. Keep out of reach of children. Flammable. Do not pour into drains, water bodies or onto the soil. Dispose of in specially designated areas.